

Walike electric pallet truck

Manufacturer		NEOlift				
Model		NTL15			NTL20	
Drive type		Electric			Electric	
Manner of operation		Walkie			Walkie	
Load Capacity	kg	1500			2000	
Load Centre	mm	600			600	
Distance between fork backrest and front wheel	mm	944			944	
Wheel Base	mm	1243			1243	
Service Weight (without battery)	kg	142			146	
Tire material		PU			PU	
Driving wheel size	Φ×w(mm)	Φ210×70			Φ210×70	
Balance wheel size	Φ×w(mm)	Φ80×60			Φ80×60	
Qty of wheel, Front/Rear (x=driving wheel)	Φ×w(mm)	Φ50×30			Φ50×30	
Qty of wheel, Front/Rear (x=driving wheel)		1x/4			1x/4	
Tread	mm	400/535			400/535	
Lifting Height	mm	200			200	
The height of handle in the operation position	mm	740/1160			740/1160	
Lowered fork height	mm	85			85	
Overall Length	mm	1603			1603	
Body Length	mm	453			453	
Overall Width	mm	550/685			550/685	
Fork Size	mm	50/150/1150			50/150/1150	
Fork Width	mm	550/685			550/685	
Ground clearance under mast	mm	35			35	
Aisle width for pallets 1000*1200 crossways	Ast (mm)	1804			1804	
Aisle width for pallets 800*1200 lengthways	Ast (mm)	1854			1854	
Turing Radius	Wa (mm)	1398			1398	
Driving Speed, load/unload	(km/h)	4.2/4.5			4.2/4.5	
Maximum gradeability load/unload	(%)	5/10			5/10	
Brake Type		Electromagnetic brake			Electromagnetic brake	
Drive Motor	(kW)	0.75			0.75	
Lift Motor	(kW)	0.8			0.8	
Battery, according to DIN 43531/35/36 A,B,C,no		no			no	
Battery voltage/rate capacity	(V/Ah)	24/30	24/40	24/60	48/20	48/30
Battery Weight (±5%)	(kg)	7.8	10.2	13.2	10.2	13.2
Type of drive control		DC			DC	
Noise level	(dB(A))	≤70			≤70	
Steering type		Manual steering system			Manual steering system	